



PCMS-4880 TRAILER-MOUNTED MESSAGE SIGN

Ver-Mac's PCMS-4880 is a mini full-matrix trailer-mounted portable changeable message sign. It features the NTCIP-compliant V-Touch controller, Tilt-and-Rotate solar panels, and JamLogic fleet management software (modem required). The PCMS-4880 is the most compact unit in our line and provides a lot of flexibility with up to 5 lines of text and 18 characters per line. It's the perfect model to use in urban areas, school zones, lower speed roadways, or for law enforcement, and special events.

HIGH-DEFINITION DISPLAY CARDS

The PCMS-4880 features Ver-Mac's exclusive high-definition display cards that provide a sharper more detailed text and graphic display. The higher degree of clarity allows the PCMS-4880 to be more visible from a distance than other message signs.



V-TOUCH CONTROLLER

NTCIP COMPLIANT

EASY-TO-READ

7-inch (178 mm) color LCD pressure-sensitive display screen

USER-FRIENDLY

One-click icon-based menu items

TIME-SAVING

Create your own library of messages

SIMPLE TO OPERATE

The intuitive point-n-go icons ensure quick and easy commands to display or edit messages

ADDITIONAL FUNCTIONALITIES

Scheduling, sign diagnostics, pin-protected security, and much more





JAMLOGIC® FLEET MANAGEMENT SOFTWARE

Equip the PCMS-4880 with Ver-Mac's high-speed modem with GPS and maximize your productivity, efficiency and profitability all remotely from your office or home! The JamLogic software is FREE and you get all the updates at no charge!

- Monitor, maintain and manage your signs from any PC, laptop, tablet or smartphone
- View your equipment in a list and GPS map view
- Change a message on one or more signs simultaneously with a simple click
- View your messages and battery voltages
- Group your signs in folders (by customer, location, project... you choose!)
- Receive e-mail or text alerts – optional (low battery cellular failure, etc.)

DISPLAY

- Display panel: 36 in x 56 in (926 mm x 1422 mm)
- Panel construction: Aluminum
- Full matrix (48 x 80 pixels)
- Up to 5 lines and 18 characters per line*
- 1 LED per pixel
- Display sign rotates 360 degrees
- Plug & play display modules

*With a 3 x 7 pixel font

WARRANTY

- 1-year warranty on complete trailers
- 2-year warranty on electronic components manufactured by Ver-Mac

DIMENSIONS AND WEIGHTS

- Operating length: 76 in. (1927 mm)
- Operating width: 62 in. (1587 mm)
- Operating height: 167 in. (4247 mm)
- Traveling height: 94 in. (2399 mm)
- Travelling length: 105 in. (2670 mm)
- Weight (approx): 1,385 lb (628 kg)
- Axle/suspension: 2,000 lb (909 kg)

OPTIONS

- Battery charger
- Modem with GPS
- Data plan (requires modem)
- Radar
- Data logger (requires radar)

Other options are available to meet your needs.

POWER SUPPLY CONFIGURATION

TILT-AND-ROTATE SOLAR PANELS

Panels tilt up to a 60-degree angle to provide maximum solar recharging during all four seasons.

- Designed to run 12 months in most regions without manual charging
- Various configurations of solar panels and batteries are available to meet your needs.

HIGH-QUALITY CONSTRUCTION

POWDER COATING SUPERIOR FINISH

Impact, humidity, salt spray and rust resistant

4 LEVELING JACKS

For stabilization and easy transportation

REMOVABLE TONGUE

For easy storage

MANUAL LIFT MECHANISM

For a quick deployment

HEAVY-DUTY PLASTIC FENDERS

For durability and easy replacement

PLASTIC BATTERY BOX

To minimize battery corrosion

LOCKABLE CONTROL BOX

For security

2-IN. (51 MM) COUPLER OR 3-IN. (76 MM) PINTLE EYE

For easy towing

APPLICATIONS

- City and county (urban areas)
- School zones
- Law enforcement
- Special events

