

FULL-SIZE, 3-LINE PORTABLE CHANGEABLE MESSAGE SIGN PCMS-1210

With its high-contrast 3-line display, our large PCMS-1210 is the ideal changeable message sign for highway work zones.

Durable and easy to set up, it is managed remotely to maximize the safety of your workers while saving them time.

Powered by Ver-Mac's robust battery/solar power management system, the PCMS-1210 provides an excellent return on investment for years to come.



PRO SERIES FEATURES

STEALTH TECHNOLOGY

- Maintenance-free batteries
- Anti-theft hidden battery compartment

V-TOUCH CONTROLLER

- Integrated 4G modem
- 10 year cell plan

HIGH PERFORMANCE LEDS

- Brighter with greater angularity
- Greater power efficiency for longer autonomy

JAMLOGIC® SOFTWARE

- Hourly automated status and battery/GPS alerts & reports
- Interactive map & list view of all equipment
- Project folders to organize equipment
- Logs date/time of all remotely activated messages

CONNECTED DEVICE


- Compatible with the Connected Work Zone (CWZ)* data-sharing feeds

**Previously the Work Zone Data Exchange (WZDx)*

APPLICATIONS

- Highway construction
- Smart work zones
- Special events
- Connected work zones

3 WAYS TO CHANGE A MESSAGE



ON THE SIGN

Using our V-Touch Controller



NEAR THE SIGN OR REMOTELY

Using JamLogic® Web on your tablet or smartphone



REMOTELY

Using JamLogic® software on your computer or laptop

DURABLE, EASY TO USE

SUPERIOR POWDER COATING FINISH

Impact, humidity, salt spray and rust resistant

4 LEVELING JACKS

Stabilization and easy transportation

TONGUE WHEEL JACK

Easy and safe trailer setup

ELECTRO-HYDRAULIC LIFT MECHANISM

Quick and effortless deployment

RUGGED INDEXED ROD MAST BRAKE

360° rotation (6° increments and infinite positions using manual hand brake)

V-TOUCH CONTROLLER

NTCIP COMPLIANT

EASY TO READ

7-inch (178 mm) color LCD touchscreen display

USER-FRIENDLY

One-click icon-based menu items

TIME-SAVING

Create your own library of messages

SIMPLE TO OPERATE

Intuitive point-and-go icons make displaying and editing messages quick and easy



Transport position

DISPLAY

- Display panel: 75 x 132 in. (1917 x 3343 mm)
- 4 LEDs per pixel
- 3 lines of 8 characters per line
- 5 x 7 pixels (18 in.) characters
- Display sign rotates 360 degrees for perfect setup
- Plug-and-play display modules for simplified maintenance

DIMENSIONS AND WEIGHT

- Operating height: 165 in. (4179 mm)
- Overall length: 183 in. (4637 mm)
- Traveling height: 106 in. (2690 mm)
- Traveling width: 87 in. (2197 mm)
- Weight (approx.): 1,740 lbs (790 kg)
- Axle/suspension: 3,500 lbs (1588 kg)

OPTIONS

- Battery charger
 - Radar
 - Statistics (radar required)
 - Fixed camera
 - Tilt-and-rotate solar panels
- Other options are available to meet your needs.

WARRANTY

- 1 year on complete trailers
- 2 years on electronic components manufactured by Ver-Mac

